




# DEEP

CEILING RECESSED



## 1.0 LED

LED 7/10W | 350/500mA | 18Vf  
COB 3-step | excl. power supply  
aluminium powder coated  
CRI >90

0.31kg IP20 0.3-1° 36°

90

wire springs 76-79 4-27

	CODE
	112161W_
	112161S_
	112161G_
	112161B_

blade springs 76-79 min 10

	CODE
	112161W_C
	112161B_C

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	530/710	>90	3
3000K	570/770	>90	5
4000K	610/830	>90	6
1800-2850K   16V	330/450	>95	9

## ALWAYS USE

power supply | 500mA

	CODE
10W	90214405
15W dim	90224501
20W DALI	90244602

350mA power supplies on page 694

## 1.0 MR16

QR-CBC51 max. 12W | GU5.3  
12V | excl. power supply  
aluminium powder coated

0.25kg IP20 0.3-1°

90

wire springs 76-79 4-27

	CODE
	112110W0
	112110S0
	112110G0
	112110B0

blade springs 76-79 min 10

	CODE
	112110W0C
	112110B0C

## ALWAYS USE

power supply | 12V

	CODE
10W dim	90221401
25W dim	90221701
70W dim	90221904

more specs on page 699

## 1.0 PAR16

PAR16 max. 12W | GU10  
100-240VAC | 50-60Hz  
aluminium powder coated

0.29kg IP20 0.3-1°

105

wire springs 76-79 4-27

	CODE
	112120W0
	112120S0
	112120G0
	112120B0

blade springs 76-79 min 10


	CODE
	112120W0C
	112120B0C

## OPTIONAL

PAR16 LED GU10 7W | phase-cut dim

	CODE
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 701



For wireless dimming compatible with Amazon Echo Plus, Philips Hue and Homee see page 239.