







# CENO on track

## 48V SYSTEM



### 1.0

LED 6.5W | 48V | COB 3-step  
aluminium powder coated  
PC adapter

0.11kg IP20 0.3-1° 35°  
90° 360°

non dim

	CODE
	166562W_
	166562B_
	166562K_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	440	>90	3
3000K	470	>90	5

### 1.0

LED 6.5W | 48V | COB 3-step  
aluminium powder coated  
PC adapter

0.11kg IP20 0.3-1° 35°  
90° 360°

DALI dim

	CODE
	166565W_
	166565B_
	166565K_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	440	>90	3
3000K	470	>90	5

dim options on page 341

### 2.0

2x LED 6.5W | 48V | COB 3-step  
aluminium powder coated  
PC adapter

0.22kg IP20 0.3-1° 35°  
90° 360°

non dim

	CODE
	166662W_
	166662B_
	166662K_

DALI dim

	CODE
	166665W_
	166665B_
	166665K_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x440	>90	3
3000K	2x470	>90	5

dim options on page 341

available from autumn 2020

Rev. 002/2020-10